

## MATERIAL SAFETY DATA SHEET

Trade Name: InstaCote™ SE FR Isocyanate Part "A"

### Section I - General Information

Item Name: InstaCote™ SE FR Isocyanate, Part "A"

Manufacture: InstaCote, Inc.  
160 C Lavoy Road  
Erie, MI 48133

Date MSDS Prepared: December 6, 1995

Last Review Date: May 17, 2012

MSDS Preparers Name/Address: Prepared by manufacturer.

Product Description: Pre-polymerized Isocyanate Blend.

Multiple Parts Product (Y/N): Y

### Section II – Hazardous Ingredient/Identity Information

Proprietary (Y/N): Y

<u>Ingredient</u>	<u>CAS #</u>	<u>Exposure Limits (TWA)</u>
4, 4'-diphenylmethane Di-isocyanate	101-68-8	0.02 ppm ceiling limit, OSHA 0.005 ppm ACGIH TLV, TWA
Mixed Isomers	26447-40-5	0.02 ppm ceiling limit, OSHA 0.005 ppm TLV, ACGIH

### Section III-Physical/Chemical Characteristics

Appearance and Odor. Clear, amber color thick liquid with faint odor

Boiling Point: 738°F

Melting Point: 99°F

Vapor Pressure: 0.001 mm Hg @ 130°F

Vapor Density: No data

Specific Gravity: 1.140 @ 72°F

Decomposition Temp.: Above 738°F

Evaporation Rate: No data

Solubility (H<sub>2</sub>O): 0.2% by wt @ 68°F

Percent Volatiles by Volume: unknown

Viscosity: 1300 cP (Brookfield #2 spindle @ 12 rpm) 72°F

pH: Not applicable

#### **Section IV - Fire and Explosion Hazard Data**

Flash Point: 396°F C.O.C.  
Lower Explosive Limit: Not Determined  
Upper Explosive Limit: Not Determined  
Extinguishing Media/Methods: Use dry chemical, CO<sub>2</sub>, AFFF (foam). If only water is available Use very large volume. Runoff water must be temporarily retained.  
Special Fire Fighting Precautions: Full face shield, self-contained breathing apparatus with full protective gear.  
Unusual Fire/Explosive Hazards: Isocyanate and water combined react to produce carbon dioxide. Contaminated, sealed containers may rupture.

#### **Section V - Reactivity Data**

Stable (Y/N): Y  
Conditions to Avoid: High temperatures  
Materials to Avoid: Product may react vigorously with water, alcohol, amines, acids, bases.  
Hazardous Decomposition Products: Oxides of carbon, oxides of nitrogen, ammonia and trace amounts of Hydrogen cyanide.  
Polymerization: May occur. Avoid contamination with liquid water or water vapor.

#### **Section VI - Health Hazard Data**

Routes of Entry  
Inhalation (Y/N): Y, May cause respiratory tract irritation(pulmonary edema, nasal discharge, coughing, chest pain. This product may cause respiratory sensitization, in which, after repeated exposures above the occupational exposure limit, hyper-reactive responses may occur in sensitized individuals following minimal doses.  
Skin (Y/N): Y, Product exhibits skin sensitization. Some evidence indicates that skin contact may induce a respiratory sensitization reaction.  
Ingestion (Y/N): Y, May cause digestive tract and gastrointestinal tract. Systemic ingestion effects are practically non-toxic.  
Other: Y, Acute vapor exposures may temporarily cause hazy or blurred vision.  
Contact Eye/Skin Hazards: Y, Product is a mild eye and skin contact irritant.  
Carcinogenicity Data: No human or animal carcinogenic data is available.  
IARC Monographs on the Evaluation of the Carcinogenic: None

#### First Aid Procedures:

Gross Inhalation: Move victim to fresh air environment. First administer oxygen, if available. Seek immediate medical attention.

Gross Ingestion: If victim is conscious, give at least two glasses of water. DO NOT INDUCE VOMITING. Seek medical assistance.

Skin Contact - Wash affected areas with soap and water. Wash soiled clothing

### **Section VI - Health Hazard Data (cont.)**

before reuse.

Severe Eye Contact - Flush eyes with water for 15 minutes. Seek medical attention.

### **Section VII - Precautions for Safe Handling and Use**

Personal Protective Equipment (Routine Use):

Respiratory Protection: Airborne concentrations of chemical should be maintained as low as possible. If vapors or mists are formed, use NIOSH/MSHA approved air supplied respirator to prevent overexposure.

Gloves: Recommend latex, butyl rubber, or nitrile gloves.

Eye Protection: Safety goggles or glasses with face shield are recommended.

Other: Recommend Tyvek suits or coveralls.

Work Practices: This product may be used in indoor or outdoor environments.

Exposures to hazardous components are not expected to exceed permissible limits during routine daily use.

Ventilation: If vapors or mists are generated, local exhaust ventilation is recommended.

Spill/Release Procedures: For major spills, call CHEMTREC 1-800-424-9300. Ventilate area and avoid breathing vapors. Use chemical cartridge respiratory protection and full protective clothing to clean large spills or spills in confined areas. Contain spill, and prevent entry into sewers and waterways.

Neutralization Procedures: Use 0.2-0.5% liquid detergent mixed with 3-8% Ammonium hydroxide or 5-10% sodium carbonate in water. Use 10 parts of solution for one part of Spill material. Allow 30 minutes to deactivate before placing spilled material into drums. Do not mix with any other waste material.

Waste Disposal Procedures: This material is not a listed hazardous waste, nor does it exhibit any hazardous waste characteristic.

Storage/Handling Procedures: Store product in a dry environment, away from strong bases and oxidizers. Do not place in contact with copper metal, copper alloys or zinc coated metals. Purge headspace in partially use container with dry nitrogen gas.

### **Section VIII-Transportation Information:**

Bill of Lading description: Plastics, Liquid, NOI, (ISOCYANATE BLENDS), Non-Hazardous

END