

MATERIAL SAFETY DATA SHEET

Trade Name: InstaCote™ M-25 Resin, Part “B”

Section I -General Information

Item Name: InstaCote™ M-25 Resin, Part “B”

Manufacture: InstaCote, Inc.
160 C. Lavoy Road
Erie, MI 48133
Phone 734-847-5260
Fax 734-847-9008

Date MSDS Prepared: October 4, 2003
Last Review Date: May 24, 2012
MSDS Preparers Name: Thomas J. Nachtman
Product Description: Liquid aromatic polyamine/polyoxyalkyleneamine with
An ammoniacal odor of various colors
Multiple Part Product (Y/N): Y (ISO Part “A” is other half of this 2 part system)
Proprietary (Y/N): Y

Section II – Ingredient/Identity Information

<u>Ingredient</u>	<u>CAS #</u>	<u>Exposure Limits (TWA)</u>
Aromatic Amine mixture	Proprietary	
Polyoxyalkyleneamine	9046-10-0	Not established
Diethyltoluenediamine	68479-98-1	Not established

Various pigments and or dyes can be present

Product is listed or hazardous according to one or more state Right To Know (SARA III) or federal Toxic Chemical Release Inventory, or Toxic Substance Control Act Laws.

Section III Physical/Chemical Characteristics

Appearance and Odor:	Colored, viscous liquid with ammoniacal odor
Boiling Point:	Not determined
Melting Point:	Not determined
Vapor Pressure:	Not determined
Vapor Density:	Not determined
Specific Gravity:	1.014 @ 69°F
Evaporation Rate:	Not determined
Solubility (H ₂ O):	<10% by wt. @ 69°F
Percent Volatiles by Volume:	less than 0.001%
Viscosity:	855 cP (Brookfield, #2 spindle @ 12rpm, @ 69°F)
pH:	Not applicable

Section IV - Fire and Explosion Hazard Data

Flash Point:	> 275°F, P.M.C.C.
Lower Explosive Limit:	Not established
Upper Explosive Limit:	Not established
Extinguishing Media/Methods:	Use dry chemical, CO ₂ , AFFF (foam), or water.
Special Fire Fighting Precautions:	None
Unusual Fire/Explosive Hazards:	None

Section V - Reactivity Data

Stable (Y/N):	Y
Conditions to Avoid:	None
Materials to Avoid:	Strong acids and Oxidizing Agents
Hazardous Decomposition Products:	Oxides of Carbon, Oxides of Nitrogen, ammonia, aldehydes and ketones and smoke as incomplete combustion products.

Section VI - Health Hazard Data

Routes of Entry	
Inhalation (Y/N):	Y, May cause respiratory tract irritation (pulmonary edema), nasal discharge, coughing and chest pain. Prolonged exposure may result in permanent lung damage.
Skin (Y/N):	Y, Product is expected to be somewhat toxic by dermal absorption.
Ingestion (Y/N):	Y, May cause digestive tract irritation and respiratory tract irritation and lung damage upon aspiration.
Other:	Y, Acute vapor exposure may temporarily cause hazy or blurred vision.
Contact Eye/Skin Hazards:	This product is highly corrosive and may cause severe burns, redness, swelling, and blistering upon direct contact.
Carcinogenicity Data:	No human carcinogenic data is available. Evidence of limited tumor growth in animals.
IARC Monographs on the Evaluation of the Carcinogenic:	None available.

First Aid Procedures:

- Gross Ingestion: If victim is conscious, give at least two glasses of water. Do not induce vomiting. Seek immediate medical attention. Physician should evacuate stomach by means least likely to cause aspiration.
- Gross Inhalation: Move victim to fresh air environment. Seek immediate medical attention. Notify physician of corrosive nature of chemical.
- Skin Contact: Wash affected areas with soap and water. Laundry soiled clothing before reuse.
- Severe Eye Contact: Flush eyes with water for 15 minutes. Seek medical attention.

Section VII - Precautions for Safe Handling and Use

Personal Protective Equipment (Routine Use):

Respiratory Protection: In cases when excessive mists might be periodically created, use NIOSH/MSHA approved full or half face respirators with dust cartridges when pouring and mixing product.

Gloves: Recommend latex, butyl rubber, or nitrile gloves.

Eye Protection: Safety goggles, face shields or safety glasses recommended.

Other: Recommend Tyvek suits or coveralls.

Work Practices: This product is to be used both outdoors and in enclosed environments with adequate respiratory and, or ventilation controls. Do not use in presence of flames or sparks.

Ventilation: If routine indoor use is required, or in the presence of excess mist generation, local exhaust ventilation is recommended.

Spill/Release Procedures: Excess spilled product, if uncontaminated, may be cleaned and disposed of as ordinary waste. No special clean up procedures are recommended.

Neutralization Procedures:

Waste Disposal Procedures: This material is not a listed hazardous waste, nor does it exhibit any hazardous waste characteristic.

Storage/Handling Procedures: Store product in a dry environment, away from strong acids and oxidizers. Keep material stored above 50°F if possible. Protect from moisture, store material inside.

Section VIII – Transportation Information

DOT Classification: Caustic Alkali Liquids NOS (Polyoxypropylenediamine), 8
UN 1719 PG III Class 55

End