
ELASTOPOR® P 17226R RESIN/ELASTOPOR® P 1046U ISOCYANATE RIGID URETHANE FOAM SYSTEM

DESCRIPTION

ELASTOPOR® P 17226R Resin/ELASTOPOR® 1046U Isocyanate is a two-component polymeric MDI based system utilizing water and HFC245fa as blowing agents. This system is designed for insulation of discontinuous metal-faced sandwich panels.

ELASTOPOR® P 17226R RESIN COMPONENT

Appearance	Amber liquid
Odor	Slight Amine
Density, @73°F	10.6 lbs./gal.
Specific Gravity, @73°F	1.26
Resin Viscosity, @73°F	500 cps
Flash Point, ASTM 3278-89	>93°F

ELASTOPOR® 1046U ISOCYANATE COMPONENT

Appearance	Dark brown liquid
Odor	Slight aromatic
Density, @77°F	10.2 lbs./gal.
Viscosity, @77°F	700 cps
Flash Point	>400°F
Vapor Pressure, at 20°C	0.00016 mm Hg

APPLICATION

Mix Ratio, Parts by weight 100 Resin/ 100 Isocyanate

Machine Mix Reactivity:

Component Temps, Resin/Isocyanate	68°F / 80°F
Component Pressures, Resin/Isocyanate	2000psi/2000psi
Cream Time	6 seconds
Gel Time	71 seconds
Tack Free Time	90 seconds
Core Density of Bag Shot	1.50 pcf

Important! The information, data and products presented herein are based upon information reasonably available to BASF Corporation at the time of publication, and are presented in good faith, but are not to be construed as guarantees or warranties, express or implied, regarding performance, results to be obtained from use comprehensiveness merchantability, or that said information, data or products can be used without infringing patents of third parties. You should thoroughly test any application, and independently determine satisfactory performance before commercialization.

"Warning" These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

BASF Corporation
1419 Biddle Avenue
Wyandotte, Michigan 48192-3799
(734) 324-6100
(734) 324-6482 (Fax)

Revision Date:07/28/2006

Urethane Specialties

ELASTOPOR® P 17226R RESIN/ELASTOPOR® P 1046U ISOCYANATE RIGID URETHANE FOAM SYSTEM

TYPICAL PHYSICAL PROPERTIES

Molded Panel, pcf	2.25
Core Density, pcf	2.00
Skin Temperature, (F)	105-115
Perpendicular Compressive Strength @10% deflection, psi	16
Perpendicular Compressive Modulus, psi	433
Parallel Compressive Strength @10% deflection, psi	31
Parallel Compressive Modulus, psi	721
Substrate Adhesion, psi	18
k factor, BTU-IN/HR-FT ² -°F Initial	0.150
Porosity (%Closed Cells)	92
Friability (% Weight Loss)	1.8
Water Absorption (%)	1.6
Butler Chimney (% Weight Retained)	92
NBS Smoke Density	220
U.L. Subject 723 (File #R5692 - 6" Core Panels)/ASTM E-84	
Flame Spread*	20
E-84 Smoke	450
Minimum Self-Ignition Temperature	430°C (806°F)
Minimum Flash-Ignition Temperature	445°C (833°F)
Dimensional Stability, % Volume Change at 28 days	
100°F/100% RH	0.1
158°F/100% RH	0.4
158°F	0.0
200°F	0.1
-20°F @ 7 Days	0.3

*This numerical flame spread rating is not intended to reflect hazards presented by this or any other material under actual fire conditions.


Important! The information, data and products presented herein are based upon information reasonably available to BASF Corporation at the time of publication, and are presented in good faith, but are not to be construed as guarantees or warranties, express or implied, regarding performance, results to be obtained from use comprehensiveness merchantability, or that said information, data or products can be used without infringing patents of third parties. You should thoroughly test any application, and independently determine satisfactory performance before commercialization.

"Warning" These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

BASF Corporation
1419 Biddle Avenue
Wyandotte, Michigan 48192-3799
(734) 324-6100
(734) 324-6482 (Fax)

Revision Date:07/28/2006

ELASTOPOR® P 17226R RESIN/ELASTOPOR® P 1046U ISOCYANATE RIGID URETHANE FOAM SYSTEM




Important! The information, data and products presented herein are based upon information reasonably available to BASF Corporation at the time of publication, and are presented in good faith, but are not to be construed as guarantees or warranties, express or implied, regarding performance, results to be obtained from use comprehensiveness merchantability, or that said information, data or products can be used without infringing patents of third parties. You should thoroughly test any application, and independently determine satisfactory performance before commercialization.

Warning These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

BASF Corporation
1419 Biddle Avenue
Wyandotte, Michigan 48192-3799
(734) 324-6100
(734) 324-6482 (Fax)

Revision Date:07/28/2006

ELASTOPOR® P 17226R RESIN/ELASTOPOR® P 1046U ISOCYANATE RIGID URETHANE FOAM SYSTEM




Important! The information, data and products presented herein are based upon information reasonably available to BASF Corporation at the time of publication, and are presented in good faith, but are not to be construed as guarantees or warranties, express or implied, regarding performance, results to be obtained from use comprehensiveness merchantability, or that said information, data or products can be used without infringing patents of third parties. You should thoroughly test any application, and independently determine satisfactory performance before commercialization.

Warning These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

BASF Corporation
1419 Biddle Avenue
Wyandotte, Michigan 48192-3799
(734) 324-6100
(734) 324-6482 (Fax)

Revision Date:07/28/2006

ELASTOPOR® P 17226R RESIN/ELASTOPOR® P 1046U ISOCYANATE RIGID URETHANE FOAM SYSTEM




Important! The information, data and products presented herein are based upon information reasonably available to BASF Corporation at the time of publication, and are presented in good faith, but are not to be construed as guarantees or warranties, express or implied, regarding performance, results to be obtained from use comprehensiveness merchantability, or that said information, data or products can be used without infringing patents of third parties. You should thoroughly test any application, and independently determine satisfactory performance before commercialization.

Warning These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

BASF Corporation
1419 Biddle Avenue
Wyandotte, Michigan 48192-3799
(734) 324-6100
(734) 324-6482 (Fax)

Revision Date:07/28/2006

ELASTOPOR® P 17226R RESIN/ELASTOPOR® P 1046U ISOCYANATE RIGID URETHANE FOAM SYSTEM



Important! The information, data and products presented herein are based upon information reasonably available to BASF Corporation at the time of publication, and are presented in good faith, but are not to be construed as guarantees or warranties, express or implied, regarding performance, results to be obtained from use comprehensiveness merchantability, or that said information, data or products can be used without infringing patents of third parties. You should thoroughly test any application, and independently determine satisfactory performance before commercialization.

"Warning" These products can be used to prepare a variety of polyurethane products. Polyurethanes are organic materials and must be considered combustible.

BASF Corporation
1419 Biddle Avenue
Wyandotte, Michigan 48192-3799
(734) 324-6100
(734) 324-6482 (Fax)

Revision Date:07/28/2006